AGRICULTURAI TIRES



RANGE OF STARMAXX

AGRICULTURAL TIRES

DESCRIPTION

- * For load capacity and inflation pressure figures on different speed rates, please consult the producer company.
- ** Load capacity on standard speed and standard load.
- Our company is entitled to change any information in this catalogue without prior notice.
- This catalogue overrides any previous catalogues
- All figures are for reference; our company cannot be deemed responsible for printing errors.
- *** The visual content of the catalogue is only representative. To find the compatible tire for your car, please refer to the car service or authorized dealer.

RANGE OF STARMAXX AGRICULTURAL TIRES

TRACTOR FRONT

















TRACTOR REAR









TRACTOR RADIAL











TRAILER RADIAL / TRAILER





























HARVESTER RADIAL / HARVESTER



TR-130 AGROVEST Radial











FORESTRY-FLOTATION













TR10 The best tire solution for sustainable farming and productivity





Ideal 2WD tractor front tire with its special 3Rib design.

- The rib design provides ultimate steering performance during soil tillage operations also across soft and cultivated areas.
- Highly resistant to cut and wears due to its strong nylon carcass structure.
- Flexible carcass structure prevents sinking.
- Special tread design provides efficient self-cleaning.



6.00-16	6PR	TT	88/A6
7.50-16	8PR	TT	103/A6
9.00-16	8PR	TT	111/A6
11.00-16	8PR	TT	118/A6



Ideal 2WD tractor front tire with its special 3Rib design.

- Durable shoulders increase tire resistance to any kind of damage and protect the tire effectively.
- Specially rounded tread root offers high endurance to stubble impacts and fissures.
- The strong carcass structure provides longevity.
- Special tread geometry provides easy steering.
- Flexible carcass structure prevents sinking.







6.00-16	6PR	TT	88/A6
6.00-16	10PR	TT	98/A8
6.50-16	6PR	TT	91/A6
6.50-16	8PR	TT	97/A6
7.50-16	8PR	TT	103/A6





Front tire for 2WD tractors appropriate to use on field and short distance road operations.

- Tread pattern and flexible carcass structure provide excellent maneuverability without sinking into the soil.
- Improved tread compound enable high resistance against wears and cuts.
- Strong center and shoulder design provides high resistance to side impacts and tread base fatigue.
- Special tread geometry provides easy steering.
- Flexible carcass structure prevents sinking.







6.00 -16	6PR	TT	88/A6
7.50- 16	6PR	TT	98/A6
7.50- 16	8PR	TT	103/A6





Ideal 2WD tractor front tire with its special 3Rib design.

- The rib design provides ultimate steering performance during soil tillage operations also across soft and cultivated areas.
- Highly resistant to cut and wears as a result of its strong nylon carcass structure.
- Flexible carcass structure prevents sinking.
- Special tread design provides efficient self-cleaning.



SIZE

10.00 -16 8PR TT 114/A6





tire for 2WD Front tractors appropriate to use on field and short distance road operations.

- Durable shoulders increase tire resistance to any kind of damage and protect the tire effectively.
- Specially rounded tread root offers high endurance to stubble impacts and fissures.
- Offers long life thanks to the use of a wear-resistant tread compound.
- · Keep the tread pattern free from the mud by special tread design.







5.50-16	6PR	TT	86/A6
6.00-16	6PR	TT	88/A6
6.50-16	6PR	TT	91/A6
6.50-16	8PR	TT	97/A6
7.50-16	6PR	TT	98/A6
7.50-16	8PR	TT	103/A6
6.00-19	6PR	TT	93/A6
6.50-20	8PR	TT	108/A6
6.50-20	10PR	TT	115/A6
7.50-20	8PR	TT	108/A6
7.50-20	10PR	TT	115/A6





Front tire for 2WD tractors appropriate to use on field and short distance road operations.

- Tread pattern and flexible carcass structure provide excellent maneuverability without sinking into the soil. Improved tread compound enable high resistance against wears and cuts.
- Strong center and shoulder design provides high resistance to side impacts and tread base fatigue.
- Special tread geometry provides easy steering.
- Flexible carcass structure prevents sinking.







6.50-16	6PR	TT	91/A6
6.50-16	8PR	TT	97/A6
7.50-18	8PR	TT	106/A6
7.50-20	8PR	TT	108/A6





R1 tractor front tire for medium and low powered tractors.

- Offers effective self-cleaning feature and grip performance during tillage operations by its special tread geometry.
- Highly resistant to cuts and wears.
- Tread profile provides high resistance to tread base fatigue.
 - Wide and strong body provides easy grip and high traction.
- Special tread geometry provides efficient self-cleaning.







6.5/80-12	6PR	TT	80/A6
6.5/80-12	6PR	TL	80/A6
6.5/80-13	6PR	TT	82/A6





High traction R1 tractor front tire for medium and low powered tractors.

- The wide and long lugs provide comfortable drive while increasing grip capacity.
- Offers long service life thanks to the use of a wear resistant tread compound.
- Efficient self-cleaning thanks to special tread design.
- Tread profile enable high resistance to tread base fatigue.
- Wide and strong body provides easy grip and high traction
- Special tread geometry provides efficient self-cleaning.







5.00-10	4PR	TT	70/58A6
5.00-12	4PR	TT	62/A6
6.5/80-12	6PR	TT	80/A6
7.00-12	6PR	TT	83/A6
10.0/80-12	6PR	TT	98/A6
10.0/80-12	6PR	TL	98/A6
5.00-15	6PR	TT	88/A6
10.0/75-15.3	12PR	TT	114/A6
11.5/80-15.3	12PR	TT	123/A6
11.5/80-15.3	12PR	TL	123/A6
6.00-16	6PR	TT	88/A6
6.50-16	6PR	TT	91/A6
7.50-16	8PR	TT	103/A6
7.00-18	8PR	TT	106/A6
7.50-18	8PR	TT	106/A6
7.50-20	8PR	TT	108/A6
8.00-20	8PR	TT	113/A6
9.50-20	8PR	TT	107/A6





High traction R1 tractor rear tire for medium and low powered tractors.

- The wide and long lugs provide comfortable drive while increasing grip capacity.
- Offers long service life thanks to the use of a wear resistant tread compound.
- Efficient self-cleaning thanks to special tread design.
- Tread profile enable high resistance to tread base fatigue.
- Special tread geometry provides efficient selfcleaning.
- Wide and strong body provides easy grip and high traction.







8.3-24	8PR	TT	108/A6
9.5-24	8PR	TT	112/A6
11.2-24	8PR	TT	116/A6
14.9/13-24	4PR	TL	112/A6
14.9/13-24	4PR	TT	112/A6
14.9/13-24	6PR	TT	123/A6
14.9/13-24	8PR	TT	128/A6
14.9/13-24	10PR	TT	134/A6
14.9/13-24	14PR	TT	142/A6
12.4/11-24	6PR	TT	115/A6
12.4/11-24	8PR	TT	120/A6
12.4/11-24	12PR	TT	128/A6
13.6/12-24	8PR	TT	123/A6
18.4/15-26	12PR	TT	146/A6
18.4/15-26	12PR	TL	146/A6
18.4/15-26	14PR	TT	149/A6
11.2-28	8PR	TT	118/A6
12.4/11-28	6PR	TT	117/A6
12.4/11-28	8PR	TT	122/A6
13.6/12-28	6PR	TT	121/A6
13.6/12-28	8PR	TT	125/A6
14.9/13-28	6PR	TT	125/A6
14.9/13-28	8PR	TT	130/A6
16.9/14-28	8PR	TT	135/A6
16.9/14-28	10PR	TT	139/A6
16.9/14-28	12PR	TT	143/A6
14.9/13-30	8PR	TT	131/A6
14.9/13-30	10PR	TT	135/A6
16.9/14-30	6PR	TT	130/A6
16.9/14-30	8PR	TT	137/A6
16.9/14-30	10PR	TT	139/A6
16.9/14-30	12PR	TT	143/A6

16.9/14-30	14PR	TT	144/A6
18.4/15-30	6PR	TT	134/A6
18.4/15-30	8PR	TT	139/A6
18.4/15-30	10PR	TT	145/A6
18.4/15-30	12PR	TT	149/A6
18.4/15-30	14PR	TT	151/A6
12.4/11-32	8PR	TT	124/A6
16.9/14-34	8PR	TT	139/A6
16.9/14-34	10PR	TT	142/A6
16.9/14-34	12PR	TT	145/A6
16.9/14-34	14PR	TT	148/A6
18.4/15-34	8PR	TT	141/A6
18.4/15-34	10PR	TT	146/A6
18.4/15-34	12PR	TT	151/A6
18.4/15-34	14PR	TT	156/A6
12.4/11-36	8PR	TT	126/A6
12.4/11-36	14PR	TT	139/A6
13.6/12-36	6PR	TT	125/A6
13.6/12-36	8PR	TT	129/A6
13.6/12-38	8PR	TT	131/A6
13.6/12-38	14PR	TT	142/A6
14.00-38	8PR	TT	131/A6
14.00-38	10PR	TT	136/A6
15.5-38	8PR	TT	133/A6
15.5-38	10PR	TT	138/A6
15.5-38	12PR	TT	142/A6
15.5-38	14PR	TT	145/A6
16.9/14-38	8PR	TT	141/A6
16.9/14-38	10PR	TT	144/A6
16.9/14-38	12PR	TT	142/A6
18.4-38	8PR	TT	143/A6
18.4-38	10PR	TT	147/A6



Tractor rear tire suitable for field operations

- Provide excellent and extra traction in all working condition by high lugs.
- Resistant to cuts and wears thanks to its special compound.
- Strong nylon carcass structure provides optimum durability.
- Open center pattern provides efficient self-cleaning and offers high resistance to tread base fatigue.
- Safe handling on hilly or sloping grounds.







12.4/11-28	8PR	TT	122/A6
16.9/14-30	10PR	TT	139/A6
16.9/14-30	12PR	TT	144/A6





R1 tractor rear tire.

- The special lug design reduces any kind of crop damage during field operations.
- Exceptional carcass structure provides optimum durability.
- Tread profile with extra wide tread base provides perfect resistance to tread base fatigue.
- Wide and reinforced body provides easy grip, high traction and reduced slipping.
- Special tread design for tough terrains provides superior performance.
- Easy lug cleanability.







9.5-24	8PR	TT	112/A6
11.2-24	8PR	TT	116/A6
12.4/11-24	8PR	TT	120/A6
12.4/11-24	10PR	TT	124/A6
13.6/12-24	8PR	TT	123/A6
14.9/13-24	8PR	TT	128/A6
12.4/11-28	8PR	TT	122/A6
13.6/12-28	8PR	TT	125/A6
14.9/13-28	8PR	TT	130/A6
14.9/13-30	8PR	TT	131/A6
16.9/14-30	8PR	TT	137/A6
16.9/14-30	10PR	TT	139/A6
18.4/15-30	8PR	TT	139/A6
18.4/15-30	10PR	TT	145/A6
18.4/15-30	12PR	TT	149/A6
18.4/15-30	14PR	TT	151/A6
16.9/14-34	8PR	TT	139/A6
18.4/15-34	8PR	TT	141/A6
12.4/11-36	8PR	TT	126/A6
13.6/12-36	8PR	TT	129/A6
16.9/14-38	8PR	TT	141/A6



R1 tire designed for high load tractor applications

- With its specially developed tread design, it provides superior traction without damaging your crops and compacting the soil.
- With its specially developed tread compounds and lug geometry, it offers high resistance against lug fatigue and tread wear.
- Low profile structure provides excellent maneuverability and handling comfort.
- Reduced vibration with frequently placed lugs.
- Superior durability against cuts and impacts with reinforced sidewalls.
- Offers high load capacity.



SIZE

30.5L-32	12PR	TL	158/A8





General purpose R1W tractor radial tire.

- Special tread compound provides high level of resistance against wear and cuts.
- Tread profile provide exceptional traction and high performance during its' service life.
- Wider footprint provides lower soil compaction.
- Offers excellent self-cleaning capability.
- Tread profile enhances resistance against tread base fatigue.
- Ensures a comfortable riding at all terrain.
- Low rolling resistance yield fuel efficiency.
- Special tread structure improves flotation on soft terrains.







ALL SIZES TR-110/85 SERIES

9.5R 20	TL	108 A8/105 B
280/85R 20 (11.2R 20)	TL	112 A8/109 B
320/85R 20 (12.4R 20)	TL	119 A8/116 B
9.5R 24	TL	107 A8/104 B
280/85R 24 (11.2R 24)	TL	115 A8/112 B
320/85R 24 (12.4R 24)	TL	122 A8/119 B
340/85R 24 (13.6R 24)	TL	125 A8/122 B
380/85R 24 (14.9R 24)	TL	131 A8/128 B
420/85R 24 (16.9R 24)	TL	137 A8/134 B
280/85R 28 (11.2R 28)	TL	118 A8/115 B
320/85R 28 (12.4R 28)	TL	124 A8/121 B
340/85R 28 (13.6R 28)	TL	127 A8/124 B
380/85R 28 (14.9R 28)	TL	133 A8/130 B
420/85R 28 (16.9R 28)	TL	139 A8/136 B
380/85R 30 (14.9R 30)	TL	135 A8/132 B
420/85R 30 (16.9R 30)	TL	140 A8/137 B
460/85R 30 (18.4R 30)	TL	145 A8/142 B
320/85R 32 (12.4R 32)	TL	126 A8/126 B
380/85R 34 (14.9R 34)	TL	137 A8/137 B
420/85R 34 (16.9R 34)	TL	142 A8/139 B
460/85R 34 (18.4R 34)	TL	147 A8/144 B
320/85R 36 (12.4R 36)	TL	128 A8/125 B
340/85R 36 (13.6R 36)	TL	132 A8/129 B
320/85R 38 (12.4R 38)	TL	143 A8/143 B
340/85R 38 (13.6R 38)	TL	133 A8/130 B
380/85R 38 (14.9R 38)	TL	139 A8/136 B
420/85R 38 (16.9R 38)	TL	144 A8/141 B
460/85R 38 (18.4R 38)	TL	149 A8/146 B
460/85R 38 (18.4R 38) RF	TL	149 A8/146 B
520/85R 38 (20.8R 38)	TL	155 A8/152 B
520/85R 38 (20.8R 38) RF	TL	155 A8/152 B
650/85R 38 (20.8R 38)	TL	173 A8/173 B
520/85R 42 (20.8R 42)	TL	157 A8/157 B
520/85R 42 (20.8R 42) RF	TL	162 A8/162 B
520/85R 46 (20.8R 46)	TL	158 A8/155 B

TA 110/80 SERIES

260/80R 20 (8.00R 20)	TL	106 A8/103 B
480/80R 38 (18.4R 38)	TL	149 A8/149 B
480/80R 42 (18.4R 42)	TL	151 A8/148 B
480/80R 46 (18.4R 46)	TL	158 A8/158 B
480/80R 50 (18.4R 50)	TL	159 A8/159 B

TA 110/70 SERIES

200/70 R16	TL	94 A8/94 B
240/70 R16 (6.00 R16)	TL	104 A8/101 B
260/70 R16 (6.50 R16)	TL	109 A8/106 B
280/70 R16 (7.50 R16)	TL	112 A8/112 B
280/70 R18 (7.50 R18)	TL	114 A8/114 B
260/70R 20 (6.50R 20)	TL	113 A8/113 B
280/70R 20 (7.50R 20)	TL	116 A8/116 B
300/70R 20 (9.50R 20)	TL	110 A8/110 B
320/70R 20 (11.2R 20)	TL	113 A8/113 B
360/70R 20 (12.4R 20)	TL	120 A8/117 B
380/70R 20 (13.6R 20)	TL	132 A8/132 B
320/70R 24 (11.2R 24)	TL	116 A8/113 B
360/70R 24 (12.4R 24)	TL	122 A8/119 B
380/70R 24 (13.6R 24)	TL	125 A8/125 B
420/70R 24 (14.9R 24)	TL	130 A8/127 B
480/70R 24 (16.9R 24)	TL	138 A8/135 B
480/70R 26 (16.9R 26)	TL	139 A8/136 B
320/70R 28 (11.2R 28)	TL	119 A8/116 B
360/70R 28 (12.4R 28)	TL	125 A8/122 B
380/70R 28 (13.6R 28)	TL	127 A8/127 B
420/70R 28 (14.9R 28)	TL	133 A8/130 B
480/70R 28 (16.9R 28)	TL	140 A8/140 B
420/70R 30 (14.9R 30)	TL	134 A8/131 B
480/70R 30 (16.9R 30)	TL	141 A8/138 B
520/70R 30 (18.4R 30)	TL	145 A8/142 B
480/70R 34 (16.9R 34)	TL	143 A8/140 B
520/70R 34 (18.4R 34)	TL	148 A8/145 B
480/70R 38 (16.9R 38)	TL	145 A8/142 B
520/70R 38 (18.4R 38)	TL	150 A8/147 B
580/70R 38 (20.8R 38)	TL	155 A8/152 B
580/70R 42 (20.8R 42)	TL	158 A8/158 B

TA 110/65 SERIES

420/65R 24 (12.4R 24)	TL	126 D/128 B
440/65R 24 (13.6R 24)	TL	128 D/131 A8
480/65R 24 (14.9R 24)	TL	133 D/136 A8
540/65R 24 (16.9R 24)	TL	140 D/143 A8
440/65R 28 (13.6R 28)	TL	131 D/134 A8
480/65R 28 (14.9R 28)	TL	136 D/139 A8
540/65R 28 (16.9R 28)	TL	149 D/152 A8
540/65R 30 (16.9R 30)	TL	150 D/153 A8
540/65R 34 (16.9R 34)	TL	145 D/148 A8
600/65R 34 (18.4R 34)	TL	151 D/154 A8
540/65R 38 (16.9R 38)	TL	147 D/150 A8
600/65R 38 (18.4R 38)	TL	159 D/162 A8
650/65R 38 (20.8R 38)	TL	163 D/166 A8





General purpose R1W row crop tractor and sprayer tire.

- Deep lugs, and special tread compound maintain longer service life.
- Narrow profile avoids crop damage.
- Special tread compound provides high resistance against wear and cuts.
- Tread design enhances self-cleaning capability, and ensures less slippage.
- Robust carcass structure enables maximum performance under heavy loads.







ALL SIZES

TR-120/95-90-85 SERIES

210/95R 32 (8.3R 32)	TL	114 A8/114 B
230/95R 32 (9.5R 32)	TL	126 A8/126 B
270/95R 32 (11.2R 32)	TL	136 A8/136 B
210/95R 36 (8.3R 36)	TL	116 A8/116 B
230/95R 36 (9.5R 36)	TL	128 A8/128 B
270/95R 38 (11.2R 38)	TL	140 A8/140 B
230/95R 40 (9,5R 40)	TL	122 A8/122 B
210/95R 44 (8.3R 44)	TL	120 A8/120 B
230/95R 44 (9.5R 44)	TL	132 A8/132 B
270/95R 44 (11.2R 44)	TL	142 A8/142 B
300/95R 46 (12.4R 46)	TL	148 A8/148 B
230/95R 48 (9.5R 48)	TL	136 A2/125 A8
270/95R 48 (11.2R 48)	TL	144 A8/144 B
270/95R 54 (11.2R 54)	TL	157 A2/146 A8
300/95R 52 (12.4R 52)	TL	156 D/159 A8
380/90R 46 (14.9R 46)	TL	159 D/162 A8
340/85R 48 (13.6R 48)	TL	151 D/154 A8



R1W tire for high power tractors.

- Built for high HP tractors, TR-130 is designed to transmit torque to the ground more effectively on any terrain.
- Special tread geometry ensures less slippage, and better traction which yield savings on fuel.
- Wider footprint and optimized lug angle minimize soil compaction and improves crop productivity.
- Elastic structure absorbs impacts, and yields better flotation.
- Strong carcass, and high-quality tread compound ensures longer service life.
- Provides driving comfort both on the road and on the field.
- Reinforced carcass structure enables maximum performance under heavy loads.







ALL SIZES

TR-130/70-65 SERIES

600/70R 28 (18.4R 30)	TL	161 D
600/70R 30 (23.1R 26)	TL	158 D
600/70R 34 (23.1R 34)	TL	160 D
710/70R 38 (20.8R 42)	TL	171 D/174 A8
800/70R 38 (20.8R 46)	TL	178 D/181 A8
620/70R 42 (20.8R 42)	TL	166 D
710/70R 42 (20.8R 46)	TL	173 D
600/65R 28 (18.4R 28)	TL	154 D/157 A8
600/65R 42 (18.4R 42)	TL	154 D/157 A8
650/65R 42 (20.8R 42)	TL	170 D/173 A8



TR-130 IF Series



R1W tire for high power tractors.

- Tires designed to operate at 20% higher rated load than standard tires at the same air pressure.
- Highly flexible sidewalls and large footprint offer lower soil compaction.
- Perfect performance under heavy loads with lower pressure compared to traditional radial tire construction.
- Special tread design enables exceptional traction performance.
- Lower inflation pressure, and sidewall flexibility enable comfortable riding.
- Elastic structure absorbs impacts to a greater extend.
- Strong carcass, and special tread compound ensures longer service life.







ALL SIZES

TR-130/70-IF SERIES

IF 600/70R 30	TL	165 D
IF 800/70R 38	TL	184 D

IF: Improved Flexion



General purpose R1W tractor front and rear tire.

- Offers durability for a wide spectrum of applications.
- Special tread compound provides high resistance against wear and cuts.
- Special tread structure provides high traction and less sinking at soft surfaces.
- Wide footprint provides lower soil compaction.
- Strong wear-resistant compound provides high resistance against wear and cuts, offers longevity.
- Ensures a balanced steering by reduced slip at all surfaces.
- It does not sink into the ground and absorbs the impacts thanks to the elastic structure.







SIZE

TR-140/85 SERIES

340/85R 28 (13.6R 28)

TL

127 A8/124 B



HST-70 VF



Multipurpose VF (Very High Flexion) all steel radial tire designed hold up to heavier loads.

- Thanks to VF (Very High Flexion) technology shows equal loading and driving performance under low pressure levels, compare to conventional tires.
- Tread compound provides resistance to cuts and wears on asphalt, hard soil and concrete surfaces.
- Wide footprint provides lower soil compaction.
- Specially steer carcass structure offers high endurance to stubble impacts and fissures.
- Protect crops effectively by its high flexion specialty.





A



SIZE

VF 285/70R 19.5 16PR TL 150/D

VF: Very High Flexion

SM-160



Ideal trailer tire.

- Offers high loading capacity with minimum soil compaction thanks to special 3 rib tread design.
- High resistance reinforced carcass structure improves resistant performance against cuts and wears, also enables longevity.
- Offers excellent self-cleaning features.







SIZE

7.50-16 10PR TT 116/A6



SM-270



Traction type trailer tire with heavy resistance.

- With special deep and tread geometry highly resistant to cuts and tread wear.
- Durable tire thanks to its reinforced sidewalls.
- High load capacity, self-cleaning and high resistance against side impacts.







SIZE

7.50-16	TZPR	11	121/A6





Traction type trailer tire with heavy resistance.

- Suitable for transport and soil tillage operations.
- Special tread and carcass structure offers high load capacity.
- Wide and deeper tread design provides high resistance against cuts and tread fatigue.







9.00-16	12PR	TL	125/A
9.00-16	12PR	TT	125/A
9.00-16	14PR	TT	128/A
9.00-16	16PR	TT	131/A
11.5/80-15.3	16PR	TL	141 A8





Traction type trailer tire .

- Suitable for short period transport and use in the field areas.
- Special tread and carcass structure offers high load capacity.
- With its specially developed tread compound and geometry, it offers high resistance against lug fatigue and tread wear.







SIZE



Traction type trailer tire.

- Suitable for short period transport and use in the field areas.
- Special tread and carcass structure offers high load capacity.
- With its specially developed tread compound and geometry, it offers high resistance against lug fatigue and tread wear.
- It does not sink into the ground and absorbs the impacts thanks to the flexible carcass structure.







SIZE

9.00-20 14PR TT 133/A6





Special trailer tire.

- Special tread and carcass structure offers high load capacity on soft surfaces.
- With its specially developed tread compound and geometry, it offers high resistance against cuts and stubble puncture.
- It does not sink into the ground and absorbs the impacts thanks to the flexible carcass structure.







9.00-16	12PR	TT	125/A6
9.00-16	14PR	TT	128/A6
9.00-16	16PR	TT	131/A6



Free rolling tire designed to use on agricultural trailers and balers.

- Even under low air pressure and heavy load, delivers durability thanks to its strong carcass structure.
- Offers floatation as rounded shoulders and wider base spread load on the surface.
- Protect crops with low soil compaction future.
- Enables driving comfort and fuel efficiency.
- Delivers excellent self-cleaning capability thanks to its wide grooves.







ALL SIZES

500/50-17	14PR	TL	149/A8 (FRA)	137/A8 (SA)
500/50-17	16PR	TL	152/A8 (FRA)	139/A8 (SA)
500/50-17	18PR	TL	157/A8 (FRA)	145/A8 (SA)

FRA: FreeR olling Axle SA: Steer Axle





Trailer tire.

- Unique pattern design allows excellent grip and handling in any condition.
- Stable central tread section with open shoulder design offers high comfort and longer life.
- Strong sidewall construction and resistant bead construction provides excellent protection against all kind of damage.
- Good floatation and self-cleaning features.
- Fuel consumption efficiency thanks to its low rolling resistance.







400/70-20	14PR	TL	154 A8/142 A8
16.0/70-20	14PR	TL	154 A8/148 A8



Modern harvester and trailer tire.

- Low dynamic rotating resistance thanks to its 5 rib design.
- Suitable for short period transport and use in the field areas.
- Prevents from slide to sides and sinking into the ground due to its wide base area.
- High resistance against cuts and wears thanks to special tread compound.







ALL SIZES

10.0/75-15.3	10PR	TT	123/A8
10.0/75-15.3	10PR	TL	123/A8
10.0/75-15.3 RF	10PR	TL	123/A8
10.0/75-15.3	12PR	TL	126/A8
10.0/75-15.3 RF	12PR	TL	126/A8
10.0/75-15.3	14PR	TL	130/A8
11.5/80-15.3	12PR	TT	135/A6
11.5/80-15.3	12PR	TL	135/A8
11.5/80-15.3 RF	12PR	TL	135/A8
11.5/80-15.3	14PR	TL	139/A8
12.5/80-15.3	12PR	TL	139/A8
12.5/80-15.3 RF	12PR	TL	139/A8
12.5/80-15.3	16PR	TL	144/A8
400/60-15.5	14PR	TL	145/A8
400/60-15.5	16PR	TL	147/A8
10.5/65-16	10PR	TT	123/A8
340/55-16	12PR	TL	140/A8
15.0/55-17	14PR	TL	137/A8
19.0/45-17	12PR	TL	141/A8
500/50-17	14PR	TL	149/A8
10.5/80-18	14PR	TT	142/A8
12.5/80-18	14PR	TT	146/A8
13.0/65-18	14PR	TT	141/A8





General purpose trailer tire.

- It squeezes less soil with its wide base area, so provides high traction on soft surfaces.
- It provides perfect balance also on soft surfaces by preventing slide to sides.
- High resistance against cuts and tread wear with special tread geometry design.
- Special tread and carcass structure offers high load capacity.







ALL SIZES

10.0/80-12	10PR	TT	122/A8
10.0/80-12	10PR	TL	122/A8
260/70-15.3	12PR	TL	126/A8
10.0/75-15.3	10PR	TT	123/A8
10.0/75-15.3 RF	10PR	TL	123/A8
10.0/75-15.3	12PR	TL	126/A8
11.5/80-15.3	12PR	TT	135/A8
11.5/80-15.3	12PR	TL	135/A8
11.5/80-15.3 RF	12PR	TL	137/A8
12.5/80-15.3 RF	12PR	TL	141/A8
12.5/80-15.3	14PR	TL	142/A8
12.5/80-15.3	16PR	TL	144/A8



General purpose trailer tire.

- It squeezes less soil with its wide base area, so provides high traction on soft surfaces.
- It provides perfect balance also on soft surfaces by preventing slide to sides.
- High resistance against cuts and tread wear with special tread geometry design.
- Special tread and carcass structure offers high load capacity.







ALL SIZES

10.0/80-12	10PR	TT	122/A8
10.0/80-12	10PR	TL	122/A8
10.0/80-12 RF	10PR	TT	122/A8
10.0/80-12 RF	10PR	TL	122/A8





General purpose trailer tire.

- Superb resistance against stubble punctures and cuts with its special tread compound.
- It ensures high performance with its Low Section Height profile design.
- High flotation capability thanks to its wide tread design.
- Heavy load capacity and long service life due to its special durable carcass structure design.







9.5L-14SL	8PR	TL	111/B
9.5L-15SL	8PR	TT	112/B
9.5L-15SL	8PR	TL	112/B
9.5L-15SL	12PR	TL	121/B
11L-15SL	8PR	TL	113/B
11L-15SL	12PR	TL	121/B
12.5L-15SL	12PR	TL	127/B

SR-3



Trailer tire designed for free rolling axle.

- Superb resistance against stubble punctures and cuts with its special tread compound.
- It ensures high performance with its Low Section.
- Height profile design.
- High flotation capability thanks to its wide tread design.
- Heavy load capacity due to its special carcass design.
- Very durable tire thanks to it durable carcass structure.







SIZE

10.0/75-15.3 12PR TL 126/A8



TR-130 AGROVEST



R1W Harvester tire with aramid belted structure.

- Aramid belt technology provides extra protection against stubble damage compared to steel and fabric alternatives.
- · Perfect performance under heavy loads and high traction with its extra reinforced carcass and bead.
- Special tread compound is resistant against punctures.
- Special tread design enables exceptional traction and better handling on the field, as well as for tillage operations.
- Wider footprint and optimizes lug angle minimize soil compaction and crop damage.
- Elastic structure absorbs impacts and yields better floatation.







ALL SIZES

TR-130/75-65 SERIES

620/75R 26 (23.1R 26)	TL	166 A8/163 B
620/75R 30 (23.1R 30)	TL	163 A8/160 B
650/75R 32 (24.5R 32)	TL	172 A8/172 B
800/65R 32 (30.5R 32)	TL	178 A8/178 B

SB-140 AGROVEST



Radial modern harvester tire.

- Offers outstanding traction on hard and soft surfaces.
- Special tread compound extended service life whether it is used on soft or hard surfaces.
- Fuel consumption efficiency thanks to its low rolling resistance.
- High load capacity and minimum soil compaction.
- Strong construction provides excellent performance and endurance.







SIZE

SB-140/70 SERIES

400/70R 20 TL 158/146 A8



IMP-70



Harvester rear tire.

- Unique pattern design allows excellent grip and handling in any condition.
- Stable central tread section with open shoulder design offers high comfort and longer life.
- Strong sidewall construction and resistant bead construction provides excellent protection against all kind of damage.
- Good floatation and self-cleaning features.
- Fuel consumption efficiency thanks to its low rolling resistance.







16.0/70-20	14PR	TL	154 A8/148 A8
400/70-20	14PR	TL	154 A8/142 A8

TR-90



Harvester tire.

- Offers outstanding comfort and excellent traction during its service-life by special aggressive lug design.
- Keep the tread pattern free from the mud by unique lug geometry.
- High resistance against cuts and wears thanks to its strong durable carcass structure and special tread compound.
- Cost-efficient tire thanks to its performance in the field and in transport.
- Suitable for heavy duty using without no damage to corps.







18.4/15-30	16PR	TT	153/A6
18.4/15-30	14PR	TT	151/A6



TR-95



Harvester tire.

- Unique lug design and geometry efficiently keep the tread pattern free from the mud and offers outstanding traction.
- High resistance against cuts and wears with strong durable carcass structure and special tread compound.
- Strong carcass structure also provides high load capacity.







23.1-26	12PR	TT	153/A6
23.1-26	14PR	TL	156/A6
23.1-26	18PR	TL	162/A6
23.1-30	12PR	TT	151/A6
23.1-30	14PR	TL	154/A6
23.1-30	18PR	TL	160/A6
20.8-38	14PR	TT	159/A6
20.8-38	14PR	TL	159/A6



TR-330



R1 tire designed for harvester applications.

- With its specially developed tread design, it provides superior traction without damaging your crops and compacting the soil.
- With its specially developed tread compounds and lug geometry, it offers high resistance against lug fatigue and tread wear.
- Low profile structure provides excellent maneuverability and handling comfort.
- Reduced vibration with frequently placed lugs.
- Superior durability against cuts and impacts with reinforced sidewalls.
- Offers high load capacity.







SIZE

30.5L-32	18PR	TL	170/A6



SM-F18



General purpose flotation tire.

- Non-aggressive pattern design offers large footprint, reduced soil compaction and ensures perfect balance.
- Resistance against side impacts with strong structure and reinforced sidewall compound.
- Absorbs side impacts with its special sidewall compound and grips the soil perfectly and prevents the vehicle to slide to sides.
- Strong tread and strong shoulder structure enable high load capacity.







ALL SIZES

12.5/80-15.3	16PR	TL	144/A8
12.5/80-15.3 RF	12PR	TL	141/A8
400/60-15.5	14PR	TL	145/A8
400/60-15.5	16PR	TL	153 A6/149 A6
400/60-15.5	18PR	TL	155 A6/151 A6
500/60-22.5	16PR	TL	163 A8/159 B
550/60-22.5	16PR	TL	167 A8/163 B
600/50-22.5	16PR	TL	165 A8/161 B

RF: REINFORCED

SM-T18



General purpose forestry tire.

- Suitable to use on soft surfaces with nonaggressive pattern.
- Non-aggressive pattern design offers large footprint, reduced soil compaction and ensures perfect balance.
- Resistance against side impacts with strong structure and reinforced sidewall compound.
- Absorbs side impacts with its special sidewall compound and grips the soil perfectly and prevents the vehicle to slide to sides.
- Strong tread and strong shoulder structure enable high load capacity.







400/60-15.5	16PR	TL	153/149 A6
400/60-15.5	18PR	TL	155/151 A6
500/60-22.5	16PR	TL	163 A8/159 E
550/60-22.5	16PR	TL	167 A8/163 E
600/50-22.5	16PR	TL	165 A8/161 B



SM-T08



General purpose flotation tire.

- Suitable to use on soft surfaces with nonaggressive pattern.
- Non-aggressive pattern design offers large footprint, reduced soil compaction and ensures perfect balance.
- Resistance against side impacts with strong structure and reinforced sidewall compound.
- Absorbs side impacts with its special sidewall compound and grips the soil perfectly and prevents the vehicle to slide to sides.
- Strong tread and strong shoulder structure enable high load capacity.







500/60-22.5	16PR	TL	159/147 A8
550/60-22.5	16PR	TL	167/155 A8
600/50-22.5	16PR	TL	156/144 A8

Starmaxx Agricultural Tires are characterized by quality workmanship, leading edge technology, unique tread designs and excellent performance offering perfect mix of quality and value.

Our success depends on exceeding the expectations of our customers and standing behind everything we do.

Our aim is to build long term relationships with our customers by providing excellent service, quality and delivering our promises.

- * Due to developments in tire technology, contents of this brochure is subject to change without any prior notice
- * Our company is not responsible for typing errors























2019 EDITION

Starmaxx Agricultural Tires are characterized by quality workmanship, leading edge technology, unique tread designs and excellent performance offering perfect mix of quality and value.

Our success depends on exceeding the expectations of our customers and standing behind everything we do.

Our aim is to build long term relationships with our customers by providing excellent service, quality and delivering our promises.





Headquarters - Factory

Petlas Tire Industry and Trade Kındam Mahallesi Ankara - Kayseri Caddesi No: 2/1 Kırşehir / TURKEY T: +90 386 252 65 50 • F: +90 386 252 65 70

Int. Sales & Marketing

Petlas Tire Industry and Trade Ako Kule, Söğütözü Mh. 2178. Cad. No: 6 06530 Ankara / TURKEY T. +90 312 309 30 30 ● F: +90 312 309 22 66

Petlas Tire USA

1111 E. Lincolnway STE 205 Cheyenne, WY 82001 USA



